

In the Claims:

1     1.     (Currently amended) A system for deployment in space  
2           comprising:

3                 a free-flying platform equipped and adapted to carry  
4           out one or more utility functions in space;

5                 a servicing and inspection apparatus including a  
6           container that defines therein a chamber dimensioned and  
7           configured to receive said platform and that has an opening  
8           through which said platform may pass into and out of said  
9           chamber, a door movably connected to said container so as  
10          to be movable between a closed position in which said door  
11          closes said opening and an open position in which said door  
12          opens said opening, a closing mechanism connected to said  
13          door and adapted to selectively move said door to said  
14          closed position so as to retain and secure said platform in  
15          said chamber in said container, and at least one light beam  
16          device that is arranged in said container and that is  
17          connected for signal transmission so as to trigger an  
18          operation of said closing mechanism when said free-flying  
19          platform passes into a path of a light beam emitted by said  
20          at least one light beam device, wherein said closing  
21          mechanism includes a motor arranged to drive said closing  
22          mechanism so as to selectively move said door between said  
23          open position and said closed position.

1     2.     (Original) The system according to claim 1, wherein said  
2           free-flying platform has a substantially spherical outer  
3           configuration.

1     3.     (Original) The system according to claim 2, wherein said  
2           free-flying platform has no outward protrusions or  
3           projections extending outwardly beyond said substantially  
4           spherical outer configuration.

1     4.     (Original) The system according to claim 2, wherein said  
2           free-flying platform has a soft resilient outer skin  
3           forming said substantially spherical outer configuration.

1     5.     (Original) The system according to claim 1, wherein said  
2           free-flying platform is equipped with a battery, a fuel  
3           tank, maneuvering thrusters, on-board electronics, a  
4           communication transmitter and receiver, and at least one  
5           item selected from the group consisting of mission-specific  
6           instrumentation, a camera, a sensor, and a tool.

1     6.     (Original) The system according to claim 1, further  
2           comprising a space vehicle or a space station, wherein said  
3           servicing and inspection apparatus is mounted on an outside  
4           of said space vehicle or said space station.

1     7.     (Original) The system according to claim 6, further  
2           comprising a monitoring and control station that is  
3           arranged inside said space vehicle or said space station

4 and that includes monitoring, control and communication  
5 electronics enabling an astronaut in said space vehicle or  
6 said space station to monitor, control and communicate with  
7 said free-flying platform outside of said space vehicle or  
8 said space station.

Claims 8 and 9 (Canceled).

1 **10.** (Currently amended) The system according to claim 1,  
2 wherein said apparatus further comprises at least one of a  
3 positioning mark and a reflector arranged on an inner side  
4 of said door or on an inner upper rim of said container  
5 around said opening, and cooperating with said light beam  
6 emitted by said at least one light beam device.

1 **11.** (Original) The system according to claim 1, wherein said  
2 apparatus further comprises a light emitting diode arranged  
3 on an inner side of said door or on an inner upper rim of  
4 said container and adapted to be used to detect a position  
5 of said free-flying platform.

1 **12.** (Original) The system according to claim 1, wherein said  
2 container includes sloping inner walls that taper inwardly  
3 away from said opening and bound said chamber to have a  
4 tapering funnel-shape.

1     **13.** (Original) The system according to claim 1, wherein said  
2           apparatus further comprises a camera arranged in said  
3           container.

1     **14.** (Original) The system according to claim 1, wherein said  
2           apparatus further comprises a photoelectric switch that is  
3           adapted to detect a position of said free-flying platform  
4           and is arranged in said container.

1     **15.** (Original) The system according to claim 1, wherein said  
2           apparatus further comprises a cushion that is arranged on  
3           an inner side of said door and that is configured,  
4           dimensioned and positioned to press against and fixedly  
5           hold said free-flying platform in a docked position in said  
6           chamber when said door is in said closed position, and said  
7           apparatus further comprises a docking cradle that is  
8           arranged in said container on a side of said chamber  
9           opposite said opening and that is configured, dimensioned  
10          and positioned to receive and fixedly hold said free-flying  
11          platform in said docked position.

1     **16.** (Original) The system according to claim 1, wherein said  
2           free-flying platform is equipped with a battery, and  
3           wherein said apparatus further comprises an electrical  
4           power source and at least one of an electrical contact and  
5           an inductive coupling connected to said power source and  
6           arranged and adapted to supply electrical power to said

7 free-flying platform in said chamber so as to re-charge  
8 said battery of said free-flying platform.

1 17. (Original) The system according to claim 1, wherein said  
2 free-flying platform is equipped with on-board electronics  
3 and electrical connector contacts connected to said  
4 electronics, and wherein said apparatus further comprises  
5 electrical connector contacts adapted and arranged to mate  
6 with said electrical connector contacts of said free-flying  
7 platform when said free-flying platform is in a docked  
8 position in said chamber.

1 18. (Original) The system according to claim 1, wherein said  
2 free-flying platform is equipped with a fuel tank and a  
3 fuel filling connection connected thereto, and said  
4 apparatus further comprises a refueling connection arranged  
5 and adapted to connect to said fuel filling connection when  
6 said free-flying platform is in a docked position in said  
7 chamber.

1 19. (Currently amended) A system for deployment in space  
2 comprising:

3 a space vehicle or a space station;

4 a free-flying platform equipped and adapted to carry  
5 out one or more utility functions in space, wherein said  
6 free-flying platform is equipped with a battery, a fuel  
7 tank, maneuvering thrusters, on-board electronics, a  
8 communication transmitter and receiver, and at least one

9 item selected from the group consisting of mission-specific  
10 instrumentation, a camera, a sensor, and a tool, and  
11 wherein said free-flying platform has a substantially  
12 spherical outer configuration;

13 a servicing and inspection apparatus mounted on an  
14 outside of said space vehicle or said space station and  
15 including a container that defines therein a chamber  
16 dimensioned and configured to receive said platform and  
17 that has an opening through which said platform may pass  
18 into and out of said chamber, a door movably connected to  
19 said container so as to be movable between a closed  
20 position in which said door closes said opening and an open  
21 position in which said door opens said opening, a closing  
22 mechanism connected to said door and adapted to selectively  
23 move said door to said closed position so as to retain and  
24 secure said platform in said chamber in said container, and  
25 at least one light beam device that is arranged in said  
26 container and that is connected for signal transmission so  
27 as to trigger an operation of said closing mechanism when  
28 said free-flying platform passes into a path of a light  
29 beam emitted by said at least one light beam device,  
30 wherein said closing mechanism includes a motor arranged to  
31 drive said closing mechanism so as to selectively move said  
32 door between said open position and said closed position;  
33 and

34 a monitoring and control station that is arranged  
35 inside said space vehicle or said space station and that  
36 includes monitoring, control and communication electronics

37 enabling an astronaut in said space vehicle or said space  
38 station to monitor, control and communicate with said  
39 free-flying platform outside of said space vehicle or said  
40 space station.

1 **20.** (Withdrawn) A method of using the system according to claim  
2 19, comprising the steps of:

3 a) launching said space vehicle or said space station  
4 from earth into an orbit in space, while keeping said  
5 free-flying platform secured in said chamber of said  
6 servicing and inspection apparatus with said door in  
7 said closed position;

8 b) in said orbit, moving said door from said closed  
9 position to said open position and releasing said  
10 free-flying platform from said chamber;

11 c) after said step b), flying said free-flying platform  
12 in space outside of said space vehicle or said space  
13 station and performing said one or more utility  
14 functions using said at least one item selected from  
15 the group consisting of said mission-specific  
16 instrumentation, said camera, said sensor, and said  
17 tool, under control of said astronaut via said  
18 monitoring and control station inside said space  
19 vehicle or said space station;

20 d) after said step c), returning said free-flying  
21 platform into said chamber of said servicing and  
22 inspection apparatus, and then moving said door from  
23 said open position to said closed position; and

24 e) after said step d), servicing said free-flying  
25 platform in said chamber by at least one of recharging  
26 said battery and refueling said fuel tank.

**[RESPONSE CONTINUES ON NEXT PAGE]**